


HORMIGONERAS CUCHARÓN CONCRETE MIXERS

mods. CH S200•S250•H300•H350•H500•H600•H800



PowerAttachments®



Expertos en implementos
Attachments experts



APLICACIONES

Cucharas hormigoneras diseñadas para conseguir una mezcla rápida y homogénea del hormigón / cemento en construcción, la obra pública, etc...

CARACTERÍSTICAS TÉCNICAS

Fácil de adaptar a minicargadoras, micicargadoras, retrocargadoras, telescópicas, vehículos multiusos..., transmisión por cadena, tapa de seguridad (con apertura asistida en la serie H), trampilla inferior con apertura hidráulica y tubo de descarga, enganche y conexiones hidráulicas a máquina portante, cableado con conector eléctrico, disponibles válvulas reguladoras de presión según modelo, consultar.

APPLICATIONS

Concrete mixers are designed to achieve a rapid and homogeneous mix of the concrete / cement in construction, public works, etc ...

FEATURES

Easy to adapt to skid steer loaders, compact wheel loader, backhoe loaders, telehandlers, multipurpose vehicles, transmission by chain, safety cap (with assisted opening in the H series), lower hatch with hydraulic opening and discharge tube, a coupling and hydraulic connections carrier machine, with electrical connector wiring, pressure control valves are available depending on the model, consult.

MODELO (referencia)	CAPACIDAD MÁXIMA (lbs)	ANCHO CUCHARÓN (mm)	ANCHO TOTAL (mm)	PESO (kg)
CH - S200	215	1.260	1.480	290
CH - S250	280	1.260	1.480	330
CH - H300	320	1.345	1.550	375
CH - H350	380	1.590	1.700	510
CH - H500	540	1.590	1.760	590
CH - H600	670	1.590	1.760	680
CH - H800	800	1.900	2.070	760
MODEL (reference)	MAXIMUM CAPACITY (lbs)	BUCKET WIDTH (mm)	TOTAL WIDTH (mm)	WEIGHT (kg)



MODELOS CH / CH MODELS	S200	S250	H300	H350	H500	H600	H800
Ancho de trabajo (mm) / Work width (mm)	1.260	1.260	1.345	1.590	1.590	1.590	1.900
Ancho total (mm) / Total width (mm)	1.480	1.480	1.550	1.700	1.760	1.760	2.070
Diámetro hélice (mm) / Auger shaft diameter (mm)	400	480	480	480	540	620	620
• Caudal máx. (lpm) / Max. flow (lpm)	60	60	60	75	75	125	200
• Presión máx. (ba r) / Max. pressure (bar)	120	120	175	205	155	160	180
• Capacidad máx. (lbs) / Max. capacity (lbs)	215	280	320	380	540	680	800
• Peso en vacío (kg) / Empty weight (kg)	290	330	375	510	590	680	760
• Peso carga máx. (kg) / Closed cover weight (kg)	804	999	1.140	1.418	1.880	2.281	2.671